



प्रसार भारती
PRASAR BHARTI
(भारत का लोक सेवा प्रसारक)
(INDIA'S PUBLIC SERVICE BROADCASTER)
दूरदर्शन केन्द्र : अहमदाबाद
DOORDARSHAN KENDRA : AHMEDABAD
DRIVE IN ROAD, THALTEJ, AHMEDABAD 380054

BY SPEED POST



GSTN : 24AAAJPO288R1ZL email: enggstoredkham@gmail.com, Phone : (079)-26859115

ENQUIRY LETTER

Date 09 10 2023

Enquiry No. 1(2)/OB/E(E/S)/2023-24/AHM

TO,

विषय :- डीडीके अहमदाबाद में Audio Mixer की खरीद

Sub: Purchase of Audio Mixer for DDK Ahmedabad

कोटेशन प्राप्त करने की नियत तिथि	19.10.2023	Time By : 15.00 Hrs.
----------------------------------	------------	----------------------

श्रीमान,

निम्नलिखित मदों के लिए विशिष्टताओं के अनुरूप मुहरबंद कोटेशन आमंत्रित किए जाते हैं:-

Sr. No.	Description Of Item	Qty.	Specification
1.	Purchase of Audio Mixer (12 channel)	01 no	As per 'Annexure-I'

लिफाफा, जिसके ऊपर नीचे लिखा है, सामान्य नियमों और शर्तों के खंड 'ए' के अनुसार भेजा जाना चाहिए।

संविदा दर संख्या।	
नियत तारीख	
वस्तु	


कृपया नियम और शर्तों को ध्यान में रखते हुए कोटेशन प्रस्तुत किया जा सकता है, अन्यथा कोटेशन अस्वीकार कर दिया जाएगा।

टिप्पणी:

(i) फर्म या उनके अधिकृत प्रतिनिधि समापन समय के बाद अर्थात् 19.10.2023 को 15:00 बजे बोलियों के उद्घाटन में भाग ले सकते हैं।

(ii) वित्तीय बोलियां सीलबंद लिफाफों में होनी चाहिए।

निविदा <https://epublish.gov.in> और <http://prasarbharati.gov.in/pbtenders> पर भी उपलब्ध है।


(रमेश ताले)

सहायक अभियंता

कृते उप महानिदेशक (अभि.)

रमेश ताले
RAMESH TALE
सहायक अभियंता
Assistant Engineer
दूरदर्शन केन्द्र, अहमदाबाद
Doordarshan Kendra Ahmedabad

GENERAL TERMS AND CONDITION

- A. The sealed quotation should reach on or before the specified date in the enquiry letter addressed to the Dy. Director General (E), Prasar Bharati, Doordarshan Kendra, Drive in Road, Thaltej, and Ahmedabad-380054.

THE COVER SHOULD BE SUPERSCRIBED WITH THE FOLLOWING:

- a. Reference to letter of enquiry.
 - b. Due date of opening quotation.
- B. This office takes no responsibility for delay, loss or non-receipt of quotations/documents sent by post where as reserves the right to accept or reject any part of the tender without assigning any reasons.
- C. Corrections if any must be attested. All rates shall be indicated both in words as well as in figures, where there is a difference between rates quoted in words and figures, rate quoted in words will prevail. The firm has to submit the signed copy of the Terms and Conditions along with the quotation. The submission is for the acceptance of the general terms and conditions without which the quote would be rejected.
- D. Forward your quotation along with the authorization letter from the manufacture/ Authorized Dealer.
- E. RIGHT OF ACCEPTANCE:
This office reserves the right to reject the lowest tender or any or all the tenders without assigning any reason whatsoever.
- F. QUOTATIONS VALIDITY:
Quotation should be valid for a minimum period up to 31 January 2024.
- G. QUALIFYING BID:
The vendor may quote separate rates for accessories.
- H. GURANTEE TERMS:
The supplier should provide warrantee/guarantee for minimum one years and onsite support. Any parts failing during the guarantee period shall be repaired /replaced free of charge by the supplier at the installation site.
- I. Qualification Criteria
1. Bidder should have experience of minimum three years in the field of supply of Audio Mixers of professional catagories
 2. The bidder should have valid GST / PAN number. It is required to mention GST/ PAN number and must enclose copy of the registration without which bid would be rejected.

J. PRICE & STATUATORY DUTIES:

1. It should be mentioned specifically whether the price quoted includes all taxes and duties.
2. GST or other duties and levies where legally leviable and intended to be claimed should be distinctly and separately mentioned in the quotation. Where it is not done no claim for GST will be admitted at any later stage and no ground whatsoever.
3. GST registration No. and date of its validity should be mentioned.
4. This office will not issue any Form such as 'C', 'D' etc.

K. PAYMENT TERMS:

1. Payment will be made, after completion of work in good condition and submitting the invoice for the same. No advance payment will be made.
2. Payment would be in Indian Rupees by cheque/DD.
3. Payment would be made after every quarter.

L. COMPLIANCE TO ANNEXURE -I

- a) Compliance statement in respect of all the points laid down in this Specification is to be enclosed along with the offer in the format given below.
- b) Compliance statement in the format mentioned below shall only be accepted.
- c) The manufacturer/dealer should also record the performance figures of their equipment offered in the quote for which the compliance statement is enclosed. The figure so mentioned should be supported by record of these in the technical literature enclosed with the tender and reference to the page number of enclosed literature for all features and technical specifications should be mentioned in the compliance Statement. Any deviation from the specification detailed in the compliance statement is to be highlighted separately.
- d) It is advised that bidder may inspect the site before submitting the tender and clearly understanding the exact scope of the work.

Sl.No Of DD specs	DD specs	Compliance	Performance Fig. of Equipment Offered	Reference to the Page no. enclosed literature	Deviation in Case of non compliance	Optional Items if any required .to make the system compliant to DD specs	Features in the offered product which exceeds DD Specs

M. ENCLOSURES:

The firm must submit the following enclosures along with the tender.

- 1) Financial bid with all quoted items as per annexure I.
- 2) Compliance statement with respect to all the points of the specifications in Annexure-I.
- 3) Signed copy of general terms and condition by the authorized person. Printed terms and conditions of tendering firms will not be considered as forming part of their tender
- 5) Any other document mentioned elsewhere in the tender document.

The tender is liable to be rejected in the absence of the above enclosures with the sole responsibility of the tenderer.

N. THE TENDERER CAN SUBMIT THEIR BIDS, IF THEY CAN PROVIDE THE SERVICES MENTIONED ABOVE.

O. Completeness of the work

The contractor should be self sufficient to complete the work with the satisfaction services for the tenderer. Any short coming noticed at any stage is liable for the tender to be rejected, with the sole responsibility of the tenderer.

CHECK LIST

Please ensure to check the following before submitting quotation otherwise, quotation will be liable for rejection:

1	Price	Price quoted both in figures and words are correct. However price quoted in words will prevail, if there is any difference.
2	Validity of offer	Up to 31.01.2024
3	Payment terms quoted	No advance/part payment will be made. Payments will be done after on satisfactory completion of work, if accepted by this office. Payment will be made in INR only. Clearly indicate as per clause K of GTC
5	Delivery period	The work is to be completed within time frame from the date of work order.
6	Packing & forwarding charges.	Should be clearly indicated. Mentioning "EXTRA" will not be acceptable. Delivery is to be made at Doordarshan Kendra, Drive In Road, Thaltej, Ahmedabad-54
7	Payment of statutory levies/ Taxes	Levis/Taxes if any are to be clearly mentioned.
8	Compliance	Compliance as per clause 'P' confirming to technical Specification of Annexure-I.
9	Enclosures	As per clause "M" of GTC

GIRNAR

Specification of Required Audio Mixers

1. The Audio Mixer Console shall be a self contained unit, complete with Input, Output and master sections and an integral SMPS capable of operating under various AC Voltages.
2. AC Input Supply – 85V -270V
3. Input Channel – 12 mono input channel & 02 stereo input channel
4. Output Channel - A stereo Mix Master
5. Mounting – Shall possible to have to be mounted on Desktop
6. Features of Mono Input Channels – An Electronically Balanced wide range Mic & Line Input on XLR & ¼" Jack connectors with continuously variable sensitivity between – 60dBu and -5 dBu, globally switched 48V Phantom Power , a 3 band equalizer with shelving HF & LF Controls at 12 Khz and 60 Hz with 15 dB cut or Boost. An MF control continuously variable from 140Hz to 3 Khz with a q of 0.77 and cut or boost of 15 dB. 02 Auxiliary sends with individual level controls. Each Auxiliary shall be individually globally switchable to be pre-fad or post-fad sends. Routing to the mix output shall be in stereo via a pan control with -4.5 dB centre drop, along with mute & solo (PFL) functions. A Peak LED shall warn of signals within 6dB of clipping. There shall be a pre-EQ insert point on a ¼" TRS jack, and a 60mm fader shall control the overall channel signal level.
7. Features of Stereo Input Channels - An Electronically Balanced line input on ¼" jack with input gain continuously variable from 0 to +20dB. There shall be two band equalizer HF & LF shelving Controls at 12 Khz and 60 Hz with cut or boost of 15 dB. 02 Auxiliary sends shall be provided both with individual level controls and feeding sum of the stereo channels to the Aux Buses. Each Aux shall be individually globally switchable to be pre-fad or post-fad sends. Routing to the mix output shall be in stereo via a balance control along with mute & solo (PFL) functions. A Peak LED shall warn of signals within 6dB of clipping. There shall be a pre-EQ insert point on a ¼" TRS jack, and a 60mm fader shall control the overall channel signal level.
8. Master Section – a stereo playback input & record output, a stereo mix outputs, output metering, a ¼" jack Headphone output mounted on console front panel. 02 aux master outputs and a Global 48V Phantom Power switch with Led Indication. The playback inputs shall be routed to the mix outputs via a gain control when a PLAYBACK TO MIX button

is pressed and to the monitor outputs when a MONITOR PLAYBACK is pressed. Ten segment LED bar graph meters shall be used to display L-R output levels, which shall be replaced by an active SOLO signal. The main stereo mix output shall be controlled by 100mm faders and fed to electronically balanced XLR connectors. There shall be mix inserts on ¼" Jack connectors.

9. 02 auxiliary master outputs shall be fed to electronically balanced ¼" jack connectors. The output level of ¼" jack headphone and monitors feeds shall be variable and may be replaced automatically by any SOLO signal.
10. Frequency response – Mic/Line Input to any output – 20 Hz to 20 Khz +/-0.5dB
11. Input & Output Levels – Mic/Line Input Maximum Level - + 17dBu
 Line Input Maximum Level - + 30dBu
 Stereo Input Maximum Level - + 30dBu
 Mix Output Maximum Level - + 20dBu
 Headphone (200Ω) – 300mW
12. Dimension – 432mm(17")W X 90.5mm (3.56")H X 362mm (14.25")D

BILL OF MATERIAL

Sr. No.	Description	Qty	Unit Price	Total Rs.
01	Purchase of Audio Mixer (12 channel)	01 no		
			GST	
			Total Rs.	

Seal of Firm

Signature of Authorized Person